



GE-BF80FO5M5X

Outdoor bullet-type Motorized IP Network Camera with IR (F-Series)



Features

- 1/3" OV High-resolution CMOS Sensor
- 2.7-13.5mm 5X Motor Zoom Auto Focus Lens
- ONVIF Conformance
- HISILICON OS05A10 + Hi3516D
- H.265+/H.265/H.264+/H.264 Compression Method
- WDR (Wide Dynamic Range)
- Improved noise figure with the enhanced 3DNR
- One touch 3-Axis locking bracket, Easy Installation Pad
- IP66 Protection

AVAILABLE ACCESSORIES



GE-A0302

GE-A0302+GE-A0811



GE-A0302+GE-AJ0501



GE-YXH0302+GE-A0601



Specifications

| ITEM | GE-BF80FO5M5X |
|-------------------------|---|
| Imaging Sensor | 1/2.7" OV High-resolution CMOS Sensor |
| Effective Pixels | 2592(H)*1944(V), 5Mega pixels |
| TV System | PAL/NTSC |
| Scanning mode | Progressive Scan |
| S/N Ratio | ≥52dB |
| Day & Night mode | ICR by Auto, Day, Night, External, Color DN |
| WDR | WDR (ATR-EX) |
| DNR | 2D-NR, 3D-NR |
| Auto Exposure | Automatic (Priority: Frame rate/Low noise), Manual |
| Shutter Speed | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec |
| Gain Control | Automatic: ~ Max. 46.2dB / Manual: ~ Max. 46.2dB |
| Auto White Balance mode | ATW-Indoor/Outdoor, Automatic, Shade, Clear sky, Fluorescent light, Light bulb, Flame, Manual |
| Lens | 2.7-13.5mm Motorized Auto Focus Lens |
| LED | 42μ x 6PCS IR Distance 80m Max |
| Functions | Motion Detection, Privacy Mask, VCA(Video Contents Analysis), Defog, D-Zoom, HLC/BLC, Mirror/Flip, Sens-up(Slow shutter), Hue, Brightness, Contrast, Saturation, Sharpness, LDC(Lens Distortion Compensation), Auto-Flickerless, Smart IR, VerticalView |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max |
| Operating Temp | -20℃ ~ +60℃ RH95% Max |
| Dimension | 182(W) x 66(H) x 67.5(D)mm |
| Housing | IP66, Aluminum Cast, Dual window, One touch 3-Axis locking bracket, Easy Installation Pad |
| Power Source | PoE(IEEE Std. 802.3af), 8W (PoE power), DC12V±10%, 1050mA |
| NETWORK SPECIFICATION | |
| Video Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG |
| Video Resolution | 2592x1944, 2560x1440, 2048x1536, 1920x1440,1920x1080, 1280x720, 800x600, 640x480,640x360, 320x240 |
| Video Frame Rate | 2592x1944@15fps (30/25fps@2560x1440/2048x1536/1920x1080p) |
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari |
| Smart Phone | iPhone, iPad, Android, Android Pad |
| P2P | YES, Support QR Code |
| Ethernet | RJ-45 (10/100Base-T) |
| Network Time Sync. | Synchronize Computer/NTP Server, Manual |
| Video Delay | 0.3S (Within the Lan) |
| RS485 | / |
| Remote Upgrade | Using Web Browser |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,SMTP |
| Client Software | Built-In Web, ONVIF Compatible 3rd Party VMS |
| SDK Support | API, ONVIF Profile S Compliant |
| SD memory card | Optional, Support Max 128GB |
| Audio & Alarm | Not Available /Optional |

Dimension (unit:mm)

Weight

1400g



(* Design and specifications are subject to change for product improvements without prior notice.

