

GE-PT100BK5M

Outdoor Bullet IP Network PTZ 5MP Camera



Features

- H.264/H.265 Compression
- 5MP
- Mechanical WDR 140dB
- Smart IR, IR Range: 100m
- 10X Optical Zoom (f=5.1mm-51mm)
- IP66

Specifications

ITEM	GE-PT100BK5M
Image Sensor	1/2.5" Aptina 5.1MP High Performance CMOS Sensor
Effective Pixels	5MP
Signal System	PAL/NTSC
	Color: 0.002 Lux @(F1.5,AGC ON)
Minimum Illumination	B/W:0.001Lux @(F1.5,AGC ON)
	0 Lux with IR
White Balance	Auto/ ATW/ Manual
AGC	Auto/ Manual
S/N Ratio	≥ 50dB
BLC	Y
HLC	Y
Smart Defog	Y
WDR	140dB
DNR	3D
Exposure Mode	Auto/ Manual/ Iris First/ Shutter First
Shutter Time	1s-1/100000s
Day& Night	Dual-ICR
Optical Zoom	10x
Digital Zoom	Y
Privacy Masking	Y
OSD	Letters, Week, Date, Time, Total 5 Regions

General

Language	English, Spanish, Korean, Italian, Turkish, Thai, Russian Polish, French, Traditional Chinese, Simplified Chinese
Operating Conditions	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Power Supply	DC12V, POE+
Power Consumption	12.05W(IR OFF)/21.18W(IR ON)
Lightning Protection	Transient voltage 6000V
Impact Protection	IP66
Wiper	N/A
IR LEDs	4PCS Array IR LEDs + 2PCS Laser Lamp
Dimensions	39.6x19.6x16(cm)

Lens

Focal Length	5.1mm-51mm
Zoom Speed	Approx.<4s(Optical Wide-Tele)
Angle of View	55.8°(w)~3.2°(t)
Min. Working Distance	1-1.5m(Wide-Tele)
Aperture Range	F1.5-F3.0

Pan & Tilt

Pan Range	0°~200°
Pan Speed	Pan Manual Speed: 0.1° ~200°/s Pan Preset Speed: 200°/s
Preset Accuracy	±0.2°
Tilt Range	-45°~40° (Auto Flip)
Tilt Speed	Tilt Manual Speed: -45°~40°/s Tilt Preset Speed: 45°/s
Proportional Zoom	Rotation Speed Can Be Adjusted Automatically According to Zoom Multiples
3D Position	Y
Number of Preset	220
Scan	3
Cruise	8, up to 16 Presets per Cruise
Pattern	8, Each One With 600s Memory or 300 Orders
Power Loss Recovery	Y
Guard Action	Preset/ Cruise/ Pattern/ Scan
PTZ Position Display	Y
Freeze Frame	Y

Infrared

IR Distance	100m
IR Angle	Adjustable by Zoom

Interface

Audio Input	/
Audio Output	/
Ethernet	1-ch RJ45 10M/ 100M
Alarm Input	Optional
Alarm Output	Optional
On-board Storage	Optional
BNC Output & RS485	N/A
Extension	N/A



Network

Max.Image Resolution	5MP
Main Stream	5MP@15fps; 1920×1080@25/30fps; 1280×960@25/30fps; 1280×720@25/30fps;1280×720@50/60fps 704×576@25/30fps;704×480@50/60fps
Sub Stream	704×576@25fps/704×480@30fps 352×288@25fps/352×240@30fps 176×144@25fps/176×120@30fps
Third Stream	352×288@25fps/352×240@30fp
Image Compression	H.265H/H.264M/H.264B/MJPEG
Audio Compression	/
Protocols	IPV4/IPV6/HTTP/802.1x/FTP/SMTP/UPnP/SNMP DNS/DDNS/NTP/RTSP/TCP/UDP/DHCP/PPPoE
Web Browser	IE8/Firefox24 and above
System Compatibility	ONVIF (Profile S), SDK, CGI

Dimension (unit:mm)

Weight

3Kgs



(*). Design and specifications are subject to change for product improvements without prior notice.

