



## GE-PT30DK2M

Outdoor Dome IP Network PTZ Full HD Camera



### Features

- H.264/H.265 Compression
- Up to 1920x1080@30fps
- Mechanical WDR 140dB
- Smart IR, IR Range: 30m
- 4X Optical Zoom (f=2.8mm--12mm)
- IP66

### Specifications



ITEM	GE-PT30DK2M
<b>Image Sensor</b>	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
<b>Effective Pixels</b>	1920(H)x1080(V)
<b>Signal System</b>	PAL/NTSC
	Color: 0.002 Lux @(F1.5,AGC ON)
<b>Minimum Illumination</b>	B/W:0.001Lux @(F1.5,AGC ON)
	0 Lux with IR
<b>White Balance</b>	Auto/ ATW/ Manual
<b>AGC</b>	Auto/ Manual
<b>S/N Ratio</b>	≥ 50dB
<b>BLC</b>	Y
<b>HLC</b>	Y
<b>Smart Defog</b>	Y
<b>WDR</b>	140dB
<b>DNR</b>	3D
<b>Exposure Mode</b>	Auto/ Manual/ Iris First/ Shutter First
<b>Shutter Time</b>	1s-1/100000s
<b>Day&amp; Night</b>	Dual-ICR
<b>Optical Zoom</b>	4X Optical Zoom
<b>Digital Zoom</b>	Y
<b>Privacy Masking</b>	Y
<b>OSD</b>	Letters, Week, Date, Time, Total 5 Regions
<b>Lens</b>	
<b>Focal Length</b>	2.8mm--12mm
<b>Zoom Speed</b>	Approx.<4s(Optical Wide-Tele)
<b>Angle of View</b>	55.8°(w)~3.2°(t)
<b>Min. Working Distance</b>	1-1.5m(Wide-Tele)
<b>Aperture Range</b>	F1.5-F3.0
<b>Pan &amp; Tilt</b>	
<b>Pan Range</b>	355°
<b>Pan Speed</b>	Pan Manual Speed: 0.1° ~355°/s Pan Preset Speed: 355°/s
<b>Preset Accuracy</b>	±0.2°
<b>Tilt Range</b>	0°~90° (Auto Flip )
<b>Tilt Speed</b>	Tilt Manual Speed: 0°~90°/s Tilt Preset Speed: 90°/s
<b>Proportional Zoom</b>	Rotation Speed Can Be Adjusted Automatically According to Zoom Multiples
<b>3D Position</b>	Y
<b>Number of Preset</b>	16
<b>Scan</b>	/
<b>Cruise</b>	/
<b>Pattern</b>	/
<b>Power Loss Recovery</b>	/
<b>Guard Action</b>	Y
<b>PTZ Position Display</b>	Y
<b>Freeze Frame</b>	Y
<b>Infrared</b>	
<b>IR Distance</b>	30m
<b>IR Angle</b>	Adjustable by Zoom
<b>Interface</b>	
<b>Audio Input</b>	/
<b>Audio Output</b>	/
<b>Ethernet</b>	1-ch RJ45 10M/ 100M
<b>Alarm Input</b>	Optional
<b>Alarm Output</b>	Optional
<b>On-board Storage</b>	Optional
<b>BNC Output &amp; RS485</b>	N/A
<b>Extension</b>	N/A
<b>Network</b>	
<b>Max.Image Resolution</b>	1920×1080
<b>Main Stream</b>	1920×1080@25/30fps; 1280×960@25/30fps; 1280×720@25/30fps; 1280×720@50/60fps 704×576@25/30fps; 704×480@50/60fps
<b>Sub Stream</b>	704×576@25fps/704×480@30fps 352×288@25fps/352×240@30fps 176×144@25fps/176×120@30fps
<b>Third Stream</b>	352×288@25fps/352×240@30fp
<b>Image Compression</b>	H.265H/H.264M/H.264B/MJPEG
<b>Audio Compression</b>	/
<b>Protocols</b>	IPv4/IPv6/HTTP/802.1x/FTP/SMTP/UPnP/SNMP DNS/DDNS/NTP/RTSP/TCP/UDP/DHCP/PPPoE
<b>Web Browser</b>	IE8/Firefox24 or above
<b>System Compatibility</b>	ONVIF (Profile S), SDK, CGI

General	
<b>Language</b>	English, Spanish, Korean, Italian, Turkish, Thai, Russian Polish, French, Traditional Chinese, Simplified Chinese
<b>Operating Conditions</b>	Indoor: 0°~ +40° Outdoor: -40°~ +60°
<b>Power Supply</b>	DC12V, POE+
<b>Power Consumption</b>	12.05W(IR OFF)/21.18W(IR ON )
<b>Lightning Protection</b>	Transient voltage 6000V
<b>Impact Protection</b>	IP66
<b>Wiper</b>	N/A
<b>IR LEDs</b>	© 42x2PCS
<b>Dimensions</b>	14x14x12.6(cm)

### Dimension (unit:mm)

### Weight

1.1Kgs



(\*). Design and specifications are subject to change for product improvements without prior notice.

